

# Sockets for electric screwdrivers (impact wrench attachments) 1"

1"




Spring shape especially for use with electric or compressed air impact wrenches.  
With cross hole and snap ring groove for securing sockets. Internal square to DIN 3121.  
**For safety reasons must always be secured using a suitable locking pin and O-ring.**

## Sockets single hexagon

Standard:

65 3010 – DIN 3129

Material: Chrome molybdenum steel, surface burnished.



Width across flats	mm	27	30	32	34	36
--------------------	----	----	----	----	----	----

Ø 63R	<b>65 3010</b> <i>Koken</i> IMPACT hexagon socket, 1"	mm	XXX	XXX	XXX	XXX	XXX
	Ø drive output end	mm	45.3	49	51.5	54	56.5
	Length	mm	57	62	62	62	62

Width across flats	mm	41	46	50	55	60
--------------------	----	----	----	----	----	----

Ø 63R	<b>65 3010</b> <i>Koken</i> IMPACT hexagon socket, 1"	mm	XXX	XXX	XXX	XXX	XXX
	Ø drive output end	mm	62.8	69	74	80.3	86.5
	Length	mm	66	70	70	75	75

Width across flats	mm	27	30	32	34	36
--------------------	----	----	----	----	----	----

Ø 62D	<b>65 3000</b> <i>HOLEX</i> IMPACT hexagon socket, 1"	mm	XXX	XXX	XXX	XXX	XXX
	Ø drive output end	mm	54	54	54	55	57
	Length	mm	60	62	62	62	67

Width across flats	mm	41	46	50	55	60
--------------------	----	----	----	----	----	----

Ø 62D	<b>65 3000</b> <i>HOLEX</i> IMPACT hexagon socket, 1"	mm	XXX	XXX	XXX	XXX	XXX
	Ø drive output end	mm	63	70	75	81	87
	Length	mm	70	76	80	84	87

Width across flats	mm	24	27	30	32	36	41	46
--------------------	----	----	----	----	----	----	----	----

Ø 62D	<b>65 3200</b> <i>HOLEX</i> IMPACT hexagon socket, 1" extra long	mm	XXX	XXX	XXX	XXX	XXX	XXX	
	Ø drive output end	mm	54	54	54	54	57	63	70
	Length	mm	100						



65 3010



65 3000



65 3200

## Drive components / connecting parts

**Material:** Chrome molybdenum steel, surface burnished.

1"



65 3400

overall length	mm	175	330
<b>65 3400</b>	<b>HOLEX.</b>	IMPACT extension, 1"	XXX

<b>65 3600</b>	<b>HOLEX.</b>	IMPACT universal joint, 1"	XXX
overall length	mm	113	

<b>65 3650</b>	<b>HOLEX.</b>	IMPACT quick-change adapter 1"	XXX
Square drive	inch	1	
overall length	mm	100	
Drive square	inch	1	



65 3600




65 3650

**Standard:** DIN 3129

**Suitable for:** Sockets 24 – 60 mm, extensions, universal joint and converter.

<b>65 3800</b>	<b>Koken</b>	"O" ring for bits and sockets, 1"	XXX
<b>65 3900</b>		Locking pin for bits and sockets, 1"	XXX

Ø (65 3800)	mm	54
Ø (65 3900)	mm	6
Length (65 3900)	mm	45



65 3800

65 3900