

Preset counters electronic

1 or 2 presets, impulses 12-260 VAC/VDC

Display LCD, 6-digits, programmable

NE131



NE131 - LCD Preset counter

Features

- Preset counter with one or two presets
- Totalizer additional
- Display 6-digits
- Operating mode, scaling factor programmable
- Connection: Voltage pulses 12...260 VAC/VDC
- Parallel display of current value, preset and output circuit status
- Keylock input for keypad
- Programmable as a time counter

Technical data - electrical ratings

Voltage supply	85...265 VAC (50/60 Hz) 10...30 VAC/VDC
Power consumption	1.5 VA, 2 W
Display	LCD, 7-segment display, 2-lines, backlit
Number of digits	6-digits
Digit height	7 mm (count) 4 mm (preset)
Function	Preset counter
Scaling factor	0.0001...9999.99
Count mode	Adding or subtracting
Counting frequency	25 Hz (DC trigger: 1 kHz)
Data memory	>10 years in EEPROM
Reset	Button, electric or automatic
Keylock	Yes, electric (keylock)
Outputs relay	Potential-free change-over contact
Output holding time	0.01...99.99 s
Standard DIN EN 61010-1	Protection class II Overvoltage category II Pollution degree 2
Emitted interference	DIN EN 61000-6-3
Interference immunity	DIN EN 61000-6-2
Programmable parameters	Measuring units, sensor logic Decimal point Scaling factor Count mode
Approvals	UL/cUL, CE conform

Technical data - mechanical design

Operating temperature	0...+50 °C
Storing temperature	-20...+70 °C
Relative humidity	80 % non-condensing
E-connection	Plug-in screw terminals
Core cross-section	1.5 mm ²
Protection DIN EN 60529	IP 65 face with seal
Operation / keypad	Membrane with softkeys
Housing type	Built-in housing
Dimensions W x H x L	48 x 48 x 108 mm
Installation depth	108 mm
Mounting	Clip frame
Cutout dimensions	45 x 45 mm (+0.6)
Materials	Housing: Makrolon 6485 (PC) Keypad: Polyester
Weight approx.	140 g

